


SPRING 0630

POLICE SPRING RIDER



Device Specifications	
Safety zone	13,8 m ²
Length	1,10 m
Width	0,82 m
Total height	0,82 m
Free fall height	< 0,60 m
Age range	1-12 years
In accordance EN standards	1176-1:2017
Availability of spare parts	Yes
Dimension of the biggest part [cm]	103x56x2
Weight of the biggest part [cm]	10

Minimal space



MATERIAL SPECIFICATION

- Side panels and backrest made of HDPE plate, resistant to weather conditions,
- Seat made of HPL plates resistant to weather conditions,
- Steel construction elements, hot-dip galvanized and powder coated or powder galvanized and powder coated,
- Steel spring 20 mm, iron phosphorated and powder coated,
- Stainless steel bars,
- Handle made of synthetic material,
- Screws covered with plastic caps or stainless steel screws.

ADDITIONAL COMMENTS

- equipment adapted for the disabled; intended for public playgrounds,
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimmie the head, fingers or any other body parts;
- anchoring on flat surface, 70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

SURFACES

Due to the free fall height of the equipment, the EN 1176-1:2017 standard allows the following surfaces: turf/ soil (A,B,C), sand with minimal layer thickness of 30 cm (A,C), synthetic material approved for free fall of 0,60 m (A,B,C).

