ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT

Product Service

CERTIFICATE

No. Z2 021662 0311 Rev. 00

Holder of Certificate: **Kompan Design Studio & Manufacturing, Berlin GmbH**
Holzhauser Str. 139
13509 Berlin
GERMANY

Certification Mark:

Product: **Climbing equipment**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.: 713150160-02

Valid until: 2024-03-18

Date, 2019-08-27 (Jens Biesenack)

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany

A4 / 07.17

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT
TÜV SÜD

Product Service

CERTIFICATE

No. Z2 021662 0311 Rev. 00

Model(s):

COROCORD™
COR 1501, COR 1502, COR 1503, COR 1504, COR 1505, COR 1506, COR 1507, COR 1508, COR 1509, COR 1510, COR 1513, COR 1514, COR 1515, COR 1515-1, COR 1516, COR 1517, COR 1518, COR 1591, COR 1592

Parameters:

Climbing course- elements clamed between steel posts.

Elements clamped with aluminium clamps consisting of 2 half-shells between steel posts with a centre distance of 6.00 m. Posts made of hot-dip galvanised tubular steel with a riveted rubber cap, rope thickness 19-21 mm, ropes connected with stainless steel S clamps, spreader bars made of aluminium piping, membranes made of 7.5 mm thick polyester fabric, wood or plastic rungs, stands made of HDPE plastic.

COR 1501 Swaying bridge
L/W/H: 6.00/ 0.66/ 2.90 m
Max. falling height: 2.65 m

COR 1502 Climbing ramp
L/W/H: 6.00/ 0.66/ 2.90 m
Max. falling height: 2.65 m

COR 1503 Swaying seesaw
L/W/H: 6.00/ 0.66/ 2.90 m
Max. falling height: 2.85 m

COR 1504 Tensegrity
L/W/H: 6.00/ 0.75/ 2.90 m
Max. falling height: 2.50 m

COR 1505 rope slalom
L/W/H: 6.00/ 0.66/ 2.90 m
Max. falling height: 2.65 m

COR 1506 Crossed ladder
L/W/H: 6.00/ 0.66/ 2.90 m
Max. falling height: 2.65 m

COR 1507 Rope screw
L/W/H: 6.00/ 0.66/ 2.90 m
Max. falling height: 2.65 m

COR 1508 Flying carpet
L/W/H: 6.00/ 0.66/ 2.90 m
Max. falling height: 2.65 m

COR 1509 Twin pendulum seat
L/W/H: 6.00/ 0.14/ 2.90 m
Max. falling height: 1.50 m
Impact surface: 5.25 x 5.90 m

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany

A4 / 07.17

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT

Product Service

CERTIFICATE

No. Z2 021662 0311 Rev. 00

COR 1510 Trail
L/W/H: 6.00/ 0.66/ 2.90 m
Max. falling height: 2.25 m

COR 1513 Tightrope
L/W/H: 6.00/ 0.50/ 2.90 m
Max. falling height: 1.00 m

COR 1514 Stand
Ø/H: 0.50/ 2.90 m
Max. falling height: 2.90 m

COR 1515 Adventure trail
L/W/H: 6.00/ 5.92/ 2.10 m
Max. falling height: 0.55 m

COR 1515-1 Adventure trail
L/W/H: 6.00/ 5.92/ 2.90 m
Max. falling height: 1.00 m

COR 1516 Hurdles
L/W/H: 6.00/ 0.66/ 2.90 m
Max. falling height: 2.65 m

COR 1517 Discus
L/W/H: 6.00/ 0.94/ 2.90 m
Max. falling height: 2.65 m

COR 1518 Prism
L/W/H: 6.00/ 0.63/ 2.90 m
Max. falling height: 2.75 m

COR 1591 Slackline steel posts
L/W/H: 5-15/ 0.20/ 1.00 m
Max. falling height: 0.85 m

COR 1592 Slackline steel posts
L/W/H: 20-60/ 0.20/ 2.10 m
Max. falling height: 1.90 m

Tested according to: DIN EN 1176-1:2017

Production Facility(ies): 021662

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany

A4 / 07.17