



Product Service

CERTIFICATE

No. Z2 053696 3129 Rev. 00

Holder of Certificate: **KOMPAN A/S**
C.F. Tietgens Boulevard 32C
5220 Odense SØ
DENMARK

Certification Mark:



Product: **Combination playing construction**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713239851-28

Valid until: 2027-11-28

Date, 2022-12-20

(Michael Weber)

CERTIFICATE

No. Z2 053696 3129 Rev. 00

Model(s): PCM110121, PCM110221, PCM110321, PCM110621, PCM110721, PCM110821, PCM111021, PCM111321, PCM112121, PCM112321, PCM210121, PCM210321, PCM210421, PCM210821, PCM210921, PCM211721, PCM212021, PCM212121, PCM212221, PCM212321, PCM212621, PCM310121, PCM310221, PCM310921, PCM311121, PCM410121, PCM410421, PCM114121, PCM212821, PCM311321, PCM610121

Parameters:

Playground combination system based on the following parts:

Three, four and six side towers with floors in 28, 38, 58, 78, 88, 98, 118, 148, 178, 238 cm.

Attachments: Stair cases, front floors, ladders, ramps, climbing nets, climbing walls, crawling tunnels, bridges, firemen poles, sliding poles, swings, overhead ladders, overhead wheels, side panels with play activities or closed, roof in different designs, slides and slider with a curved downward track.

Steel posts pre galvanized and powder coated: Ø101x2 mm tube.

Wood posts of impregnated pine: Ø100 mm:

Side panels, roofs, floors, steps, ramps, climbing walls and platforms: 10 mm HPL, 3 mm Aluminium, 19 mm HDPE, 18 mm Eco grip plates.

Tube elements like crossbars, handrail, guardrails, fireman poles, ladder steps, track rider, swing crossbar: Ø32x2 mm, Ø38x2 mm, Ø42,4x3,2 mm, Ø48,3x4 mm, Ø76,1x4,5 mm, Ø101,2, Ø31,7x1,5 mm covered with Ø39 mm PP tubes.

Net and ropw elements: Ø16 mm PP covered steel rope.

Slides: Stainless steel, LDPE slide, LDPE segment slide or PE tunnel slide.

Tested according to: DIN EN 1176-1:2017
DIN EN 1176-3:2017
EN 1176-1:2017
EN 1176-3:2017