Kipunji Trail

CRP251001





General Product Information

Dimensions LxWxH 799x681x369 cm
Age group 6+
Play capacity (users) 32
Colour options



WOW! The Kipunji's varied range of climb, crawl and bounce thrills makes it highly attractive for children, again and again. The high variety of activities appeal to a wide age range, challenging cross-coordination skills, which again trains body confidence and spatial awareness. The triangular membrane and horizontal nets serve as spacious meeting

points, inviting children to rest and socialize amidst the physical thrills. Kipunji also invites acrobat exercises on the high bars and rocking and swaying upper body driven movements on the Overhead Rocker with UFO discs. This invites cooperation and upper body activity, which is especially important in today's sedentary lifestyles. Kipunji is a highly versatile

play piece that invites both physical and social activity.



Kipunji Trail

CRP251001







Ropes are made of UV-stabilized PES rope strands with inner steel cable reinforcement. The polyester wrapping is inductively melted onto each strand to obtain excellent wear and tear resistance.



Corocord 'S' clamps are used as universal connections in Corocord products. 8mm stainless steel rods with rounded edges are pressed around the ropes with a special hydraulic press, making them the ideal connector: safe, durable and vandalism-proof, all while allowing the typical movement of rope play structures.



Panels of 19mm EcoCore™. EcoCore™ is a highly durable, eco friendly material, which is not only recyclable after use, but also consists of a core produced from 100% recycled post consumer material from food packing waste.



Installation Information Max. fall height 214 cm Safety surfacing area 68.0 m² Total installation time 27.9 Excavation volume 15.72 m³ Concrete volume 8.60 m³ Footing depth (standard) 90 cm Shipment weight 868 kg Surface Anchoring options In-ground **Warranty Information** Hot dip galvanised steel Lifetime Painted toplayer 10 years 10 years Ropes & nets Aluminium clamps 10 years Spare parts guaranteed 10 years

Item no. CRP251001-0902



Colored steel components have a base of hot dip galvanization and a powder coated top finish. This provides an ultimate corrosion resistance in all climates around the world. Other steel surfaces are hot dip galvanized inside and outside with lead free zinc.



Corocord smart clamps are carefully designed in every detail to ensure superior flexibility in high quality aluminum material. The smart clamps are attached around the posts with four steel bolts. Not used attachment points are closed with PA caps.



Slide is made of moulded PE. PE has excellent impact strength and it is usable within a large temperature span.



Sustainability





Cradle to Gate A1-A3	Total CO ₂ emission	CO₂e/kg	Recycled materials
	kg CO₂e	kg CO₂e/kg	%
CRP251001-0902	2,216.50	3.45	40.60

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Kompan A/S

C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Validation of CO₂ calculation of: Corocord



Data version no. 2021-09-27

The CO₂ calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Corocord" represented by item no.: COR314011-1101.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 15. October 2021 | Valid until: 15. October 2023 Validated by:

Bente Hviid, Senior Consultant

Peter Bendtsen, Senior Consultant

Validation based on report: Validation of CO₂ calculation of 8 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Bente Hviid and Peter Bendtsen.

Publication date: 15. October 2021

By Bureau Veritas HSE +45 7731 1000


Kipunji Trail


CRP251001



* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height





Click to see TOP VIEW

Click to see SIDE VIEW