



#### **Product technical sheet**

# **ROBINIA RB1903**







6+

38 kids

78,0 m<sup>2</sup>



### **Material specification**

- Construction made of Robinia very durable acacia wood with a diameter of ~ 12 -18 cm without sharp edges, resistant to weather conditions,
- Platforms, gangways, side panels and seats made of Robinia very durable acacia wood, resistant to weather conditions,
- Transparent polycarbonate panels with a weather-resistant print,
- Roofs made of strong Robinia acacia wood with colorful elements made of HPL plate, resistant to weather conditions,
- Side panels made of durable HPL plate, resistant to weather conditions,
- Slides made of stainless steel,
- Colorful elements made of durable HPL plate, resistant to weather conditions,
- Moving elements made of durable HPL plate, resistant to weather conditions,
- Telescope made of stainless steel and durable HDPE plate, resistant to weather conditions,
- Flags made of HPL plate, resistant to weather conditions, mounted on a stainless steel structure.
- Windows made of Plexiglas mirrors in a safe cover made of HPL plate, resistant to weather conditions,
- Elements made of safe, certified rubber with textile reinforcement,
- Grates made of safe, certified rubber with textile reinforcement,
- Climbing stones made of durable HPL plate, resistant to weather conditions, and stainless steel,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Rubber hammock with textile reinforcement,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Handles made of steel rope in polypropylene braid,
- Screws covered with plastic caps and/or stainless steel screws,



#### Facilitating disability



easy access

integration



shelters



Intellectual development



manipulation



thinking



### **Physical development**



balance

slidina



hiding

rest



observation





passage



climbing



roofs

**Vinci Group Sp. z o.o.** Seminaryjna 9 Street 99-400 Łowicz VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26

M: +48 793 404 991












# Product technical sheet ROBINIA RB1903

## **Product data**



Data is subject to change without prior notice.


#### **Additional information**

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;






**10** number of activity elements







## Guarantee



30 year guarantee -Durability of steel and **1** stainless steel structural elements



15 year guarantee - Durability of steel and stainless steel structures of mobile devices; durability of Robinia wood structural elements



10 year guarantee - Structural strength of HDPE, 100% recycled HDPE and HPL elements; structural elements made of 100% recycled material (composite)



5 year guarantee - Corrosion resistance of stainless steel and hot-dip galvanized and powder-coated steel elements, resistance to bark beetles and rotting of wooden structural elements

Detailed information in the guarantee card

**Vinci Group Sp. z o.o.** Seminaryjna 9 Street 99-400 Łowicz VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991



biuro@vinci-play.com info@vinci-play.com www.vinci-play.com



# **Surfaces according to EN 1176-1:2017+A1:2023**

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C)	Particle size from 20 to 80	30	≤200
		40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		250

## **Product technical sheet**

# **ROBINIA RB1903**

# Amount of safe surface corresponding with free fall height:

HIC <60	21,7 m <sup>2</sup>
HIC 100	5,1 m <sup>2</sup>
HIC 120	0,4 m <sup>2</sup>
HIC 150	5,1 m <sup>2</sup>
HIC 190	1,6 m <sup>2</sup>
HIC 220	16,9 m <sup>2</sup>
HIC 250	27,2 m <sup>2</sup>

Data is subject to change without prior notice.

